


DME XPress Mold Bases



DME XPress™ A-Series Mold Base

PREMIUM STEEL, INTERCHANGEABLE PLATES, FULLY FEATURED

The DME XPress mold base sets the standard for fast delivery with **58,000 combinations**.



THE DME XPRESS ADVANTAGE

Stress Relieved & Pre-Hardened Steel

- Increases your cutting speeds
- Reduces machine center spindle time
- Avoid unnecessary downtime
- Extended tool life
- DME #3 premium P20 steel - "Machined 4 Quality"

Interchangeable plates

- Precision machined
- Repeatable
- Replacement plates, online and easy to order

Off the Shelf

- 58,000 configurations
- Engineered and validated
- Quick shipment*

Immediate Quotes and Orders - eStore

- Configurable mold base
- Real-time pricing on-line 24/7
- Add to , Order
- Emailed confirmation

Configure, Price, Order < 1 Minute

Contact DME

For more information or delivery options contact at:
800-626-6653 (U.S.) • 800-387-6600 (Canada) • 248-398-6000 (Worldwide).

www.dme.net/xpress

<https://dme.net/estore>

Keyword search: **XPRESS**

*Most popular sizes are stocked, some sizes may require additional time to ship

IT'S ALL IN THERE!

STANDARD MOLD BASE FEATURES INCLUDE:

- 7 Plate A-Series Design
- 23 Sizes – 8"x 8" to 19"x 24"
- 9 A/B-Plate thicknesses – 7/8" to 5-7/8"
- 162 A/B-Plate combinations
- Rail Heights 2.5" - 4.5"
- #3 Premium P20 steel for A and B-Plates
- Steel Finish Ground $\pm .001$ "
- Center Holes - A-side only (optional)
- Guided Ejection - System #3 (optional)
- Return Pins – inboard (prevents spring breakout)
- Locating Ring (optional)
- Sprue Bushing (optional)
- Lift Holes - Top Clamp/Support plates
- Vented Leader Pins
- Type C Clamp Slots
- Pry Bar Slots on parting line and ejector plate
- Chamfering on all plate edges
- Stop Disks
- 3-Piece Ejector Housing with shoulder bolts

XPRESS MOLD BASE STEEL

DESCRIPTION	STEEL	T	W X L
Top Clamp Plate	#2	± 0.001	± 0.002
A-Plate	#3	± 0.001	± 0.002
B-Plate	#3	± 0.001	± 0.002
Support Plate	#2	± 0.001	± 0.002
Rails	#1	± 0.001	+0/-0.004
Ejector Retainer Plate	#1	± 0.015	+0/-0.004
Ejector Plate	#1	± 0.015	+0/-0.004
Bottom Clamp Plate	#1	± 0.001	± 0.002





DME XPress™ A-Series Mold Base

TO ORDER AN XPRESS MOLD BASE:

Go to the DME eStore configurator: dme.net/configurator

Click on DME XPress A-Series tab and configure your XPress mold base through the following steps.

- 1 Configure your new mold base by choosing one choice for each selection option.
- 2 Sprue Bushing "O" 3 Sprue Bushing "R" 4 Locating Ring

Example Part Number for highlighted selections: **XPA1012 -17 -17 -35 -GE -3**

1		XP	A	1012	-17	-17	-35	-GE	-3			
FAMILY	SERIES	BASE	SIZE (W" X L")	AP	THICKNESS	BP	THICKNESS	RAIL	HEIGHT	EJECTION	A/B PLATE MATERIAL	
XP	A	A Series	0808	7.875 x 7.875	7*	0.875"	7	0.875"	25 [†]	2.50"	GE	Guided Ejection
XP	B	B Series	0812	7.875 x 11.875	13*	1.375"	13	1.375"	30	3.00"		
			1008	9.875 x 8	17	1.875"	17	1.875"	35	3.50"	NG	No Guided Ejection
			1012	9.875 x 11.875	23	2.375"	23	2.375"	40	4.00"		
			1016	9.875 x 16	27	2.875"	27	2.875"	45	4.50"		
			1112	10.875 x 12	33	3.375"	33	3.375"				
			1114	10.875 x 14	37	3.875"	37	3.875"				
			1118	10.875 x 18	47	4.875"	47	4.875"				
			1212	11.875 x 12	57	5.875"	57	5.875"				
			1215	11.875 x 15	7NCH*	0.875"						
			1220	11.875 x 20	13NCH*	1.375"						
			1315	13.375 X 15	17NHC	1.875"						
			1318	13.375 X 18	23NHC	2.375"						
			1321	13.375 X 20.75	27NHC	2.875"						
			1518	14.875 x 17.875	33NHC	3.375"						
			1524	14.875 x 23.75	37NHC	3.875"						
			1616	15.875 x 16	47NHC	4.875"						
			1620	15.875 x 20	57NHC	5.875"						
			1623	15.875 x 23.5								
			1818	17.875 x 18								
			1820	17.875 x 20								
			1823	17.875 x 23.5								
			1924	19.5 x 23.75								



- A & B-Series plates with no additional letters include center hole in the TCP & AP, or AC plates.
 - **NCH** = No center hole in the TCP and the AP plate for the A-Series or the AC plate for B-Series
 * 7/8" and 1 3/8" available only in the A-Series
 † = 2.5" Rails only available in base sizes 0808 to 1118

2		3		4	
0 - 7/32"		R - 1/2"		L - 6501	
SPRUE ORIFICE	SPRUE RADIUS	LOCATING RING	DESCRIPTION		
0	5/32"	L	6501	3.99 Ø Standard	
	7/32"		6521	3.99 Ø Standard, Extra Length	
	9/32"		6504	3.99 Ø Clamp Type	
	11/32"			Omit	
	Omit				

- 5 DOWNLOAD CAD
- 6 SELECT A QUANTITY
- 7 ADD TO ORDER

[Click here for standard XPress Return Pin and Stop Disc locations](#)

XPRESS MOLD BASE STEEL COMPOSITION

- #1 Steel:** AISI 1045, 1.1730 or equivalent, stress-relieved, annealed
- #2 Steel:** AISI 4130, 4140 or equivalent, stress-relieved, pre-hardened, 28-34 HRC
- #3 Steel:** AISI P20, DIN 1.2311, G40CrMnMo7 or equivalent, stress-relieved, pre-hardened, 28-35 HRC

XPRESS MOLD BASE SUPPORT MATERIAL

- 3D CAD data available for download: Solidworks® Parametric, Creo, & Parasolid drawings
- Product Specifications
- Product Features
- ONE YEAR Manufacturers Warranty